

» AM4510 «



SSD AMC module for the ultimate in storage performance

- » Intel® X25-E SATA Solid State Drive (SSD)
- » 32 GB and 64 GB storage capacity
- » PICMG AMC.0 R2.0 / AMC.3 R1.0
- » Enhanced performance, reliability, ruggedness and power savings

Superior read/write access times and I/O

The popularity of AMC storage solutions continue to evolve

The Kontron AM4510 SATA storage AMC modules uses Intel's leading SSD for Native Serial Advanced Technology Attachment (SATA) hard disk drive, and achieves enhanced performance, reliability, ruggedness and power savings. Since there are no rotating platters, moving heads, fragile actuators, unnecessary pinup time or positional seek time that can significantly slow down the storage subsystem, the Intel X25-E SATA

SSD enables fast read/write access times and significant I/O, as well as performance improvement when compared to rotating media. The new Kontron AM4510 AMC module will be offered with a 64GB storage capacity and will be compatible with Kontron's family of AdvancedTCA processor and carrier blades as described by the PICMG AMC.0 R2.0 and AMC.3 R1.0 specifications.

Technical Information	
Hard Disk Features	Storage capacity: 32GB and 64GB
Access	75 microseconds
Sequential Bandwidth R/W	250 / 170 MB/s Sustained 300MB/s burst
Characteristics	NEBS level 3; 24 hours / 7 days operation
Compliance	PICMG AMC.0 R2.0 / AMC.3 R1.0
IPMI Features	Management Controller compliant to PICMG 3.0, AMC.0 and IPMI v1.5 rev 1.1; Management Controller is run time field reprogrammable without payload impact; Robust fail safe reprogramming implementation (which includes two firmware images) that could perform automatic or manual rollback if a problem occurs during critical reprogramming phase; Remote upgrade capability from all IPMI interfaces (via IPMB)
Supervisory	Hardware system monitor through IPMI (voltage, currents, temperature), temperature monitor / alarm; board temperature sensor, power failure
Mechanical	181.5 x 75 x 30.16 mm, single-width full-size; 181.5 x 75 x 18.96 mm, single-width mid-size; Weight: 350 g
Power Requirements	Management power is less than 100mA peak at 3.3 V, Payload power is 6 W
Environmental Temperature*	Operating: 0-70° C / 32-158° F; Storage and Transit: -40 to +70° C / -40 to 158° F
Environmental Humidity*	Operating: 15% to 90% @55° C/131° F non-condensing; Storage&Transit: 5% to 95% @ 40° C/104° F non-condensing
Environmental Altitude*	Operating: 4,000 m / 13,123 ft; Storage and Transit: 15,000 m / 49,212 ft
Environmental Shock*	Operating: 30G, half-sine 11ms, each axis; Storage and Transit: Bellcore GR-63-CORE Section 4.3
Environmental Vibration*	Operating: 1.0G, 5-500Hz each axis; Storage and Transit: 0.5G, 5-50Hz; 3.0G, 50-500Hz each axis
Safety / EMC	Meet or exceed: Safety: UL 60950-1; CSA C22.2 No 60950-1-03; EN 60950-1:2001; IEC60950-1 EMI/EMC: FCC 47 CFR Part 15, Class B; CE Mark to EN55022/EN55024/EN300386
Warranty	Two years limited warranty

* Designed to meet or exceed

CORPORATE OFFICES

Europe, Middle East & Africa

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany

Tel.: +49 (0) 821 4086-0
Fax: +49 (0) 821 4086 111
sales@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA

Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building,Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China

Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn