

» CP-ASM3 «



Ready available 3U CompactPCI® Card Cages

- » 19" Racks with RIO and FAN Options
- » Industrial Power Supplies from 14 VDC to 260 VAC
- » Backplanes with 2 to 8 Slot Segments
- » EMI protected and CE compliant

CP-ASM3 is a series of ready integrated standard card cages for 3U CompactPCI®, based on the quality and experience of the technology leader.

CompactPCI® is the most accepted modular standard throughout the ICT market segments. CompactPCI® is loved for any application, where openness, modularity, robustness, reliability, or longevity is an advantage. It provides outstanding.

- » **Flexibility:** just plug another I/O board where needed
- » **Variability:** upgrade to another CPU for higher performance
- » **Longevity:** switch over to next generation CPU blade
- » **Supplier-independency:** for special needs, select any market available component

Technical Information

Dimensions

84HP Rack	483 x 133 x 282mm / 84HP, 3U, 275mm
42HP Rack	220 x 133 x 242mm / 42HP, 3U, 235mm
84HP Fan Tray	483 x 45 x 282mm / 84HP, 1U, 275mm
42HP Fan Tray	220 x 45 x 242mm / 42HP, 1U, 235mm

P47-Style Power Supply

200 Watt AC

CP3-SVE-P200AC

» Input: 85-264 VAC	» Cooling: Forced airflow mandatory!
» Max Output: 5V/40A, 3.3V/40A, +12V/5.5A, -12V/1.5A.	» Characteristics: Hot swapable, redundant
» Dimension: 3U, 8HP	

200 Watt DC 36 - 75 VDC

CP3-SVE-P200DC

» Input: 36 - 75 VDC	» Cooling: Forced airflow mandatory!
» Max Output: 5V/40A, 3.3V/40A, +12V/5.5A, -12V/1.5A.	» Characteristics: Hot swapable, redundant
» Dimension: 3U, 8HP	

200 Watt DC 18 - 36 VDC

CP3-SVE-P200DC

» Input: 18-36 VDC	» Cooling: Forced airflow mandatory!
» Max Output: 5V/25A, 3.3V/36A, +12V/3A, -12V/0.5A	» Characteristics: Hot swapable, redundant
» Dimension: 3U, 8HP	

M-Style Power Supply

180 Watt AC

CP3-SVE-M180AC

» Input: 85-264 VAC	» Cooling: Free convection airflow
» Max Output: 5V/20A, 3.3V/14A, +12V/2A, -12V/1A.	» Characteristics: Not hot swapable, not redundant
» Dimension: 3U, 12HP	

150 Watt DC

CP3-SVE-M150DC

» Input: 36-76 VDC	» Cooling: Free convection airflow
» Max Output: 5V/14A, 3.3V/14A, +12V/2A, -12V/1A.	» Characteristics: Not hot swapable, not redundant
» Dimension: 3U, 12HP	

100 Watt DC

CP3-SVE-M100DC

» Input: 14,4-154	» Cooling: Free convection airflow
» Max Output: 5V/10A, 3.3V/12A, +12V/9A	» Characteristics: Extended temperature, conformal coating, EN50155
» Dimension: 3U, 12HP	

For further information refer to the respective manuals of the power supplies or CompactPCI® backplanes.



CP-ASM4R-84F-P200AC-B0800-STD

Technical Information

CompactPCI® Backplane

for P47 style PSU

CP3-BP8-P47-RIO
 » PSU connector: P47
 » Slot: 8, all 32 bit with Rear I/O
 » System slot: right

for M-style PSU

CP3-BP8-M-RIO
 » PSU connector: M-style
 » Slot: 8, all 32 bit with Rear I/O
 » System slot: right

1U Fan Tray

84HP / 1U-275mm / 3.6W

CP-MKIT-FAN-84-3
 » Power consumption: 12 VDC / 3x 1.2 Watt
 » Airflow: 3x 95m³/h (56cfm) / average of 1.25 m/s (250lfm)

84HP / 1U-275mm / 15W

CP-MKIT-FAN-84-15
 » Power consumption: 12 VDC / 3x 5 Watt
 » Airflow: 3x 170m³/h (100cfm) / average of 2.5 m/s (500lfm)

42HP / 1U-235mm / 1.2W

CP-MKIT-FAN-42-1
 » Power consumption: 12 VDC / 1x 1.2 Watt
 » Airflow: 1x 95m³/h (56cfm) / average of 0.8 m/s (160lfm)

42HP / 1U-235mm / 5.6W

CP-MKIT-FAN-42-5
 » Power consumption: 12 VDC / 4x 1.4 Watt
 » Airflow: 4x 56m³/h (33cfm) / average of 1.1 m/s (220lfm)

Disk Drive Assembly Kits

Single 2.5" SATA HDD/SSD

CP-HDD-S-KIT-S

Double 2.5" SATA HDD/SSD

CP-HDD-S-KIT-D

General*

Ambient temperature

0°C to +50°C

Humidity

Up to 93% RH at 40°C, non-condensing (acc. To IEC 60068-2-78)

Protection

IP20

Over voltage category

2

Protection class

1

EMI

EN55022 / EN55024

Safety

EN60950-1

* All systems described in the ordering list are conform to or better than.



CP-ASM3R-84-M100DCWV-B0800-STD

Ordering Information

Article *

CompactPCI® Card Cage 84HP[CP-ASM3R-84-P200AC-B0800-STD](#)[CP-ASM4R-84F-P200AC-B0800-STD](#)[CP-ASM3R-84-P200DC48V-B0800-STD](#)[CP-ASM4R-84F-P200DC48V-B0800-STD](#)[CP-ASM3R-84-P200DC24V-B0800-STD](#)[CP-ASM4R-84F-P200DC24V-B0800-STD](#)[CP-ASM3R-84-M180AC-B0800-STD](#)[CP-ASM4R-84F-M180AC-B0800-STD](#)[CP-ASM3R-84-M100DCWV-B0800-STD](#)[CP-ASM4R-84F-M100DCWV-B0800-STD](#)[CP-ASM4-84F-M100DCWV-B1100-STD-SWMP](#)**CompactPCI® Card Cage 42HP**[CP-ASM3-42-M100DCWV-B0400-STD](#)[CP-ASM4-42F-M100DCWV-B0400-STD](#)[CP-ASM4R-44F-M180AC-B0500-STD-TT](#)**Disk Drive Assembly Kits**[CP-HDD-S-KIT-S](#)[CP-HDD-S-KIT-D](#)[CP-MKIT-CDROM](#)[CP-DVDRW-SATA](#)

Description

3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt AC PSU and 8 slot backplane, 4U variant including 1U fantray

3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt 48VDC PSU and 8 slot backplane, 4U variant including 1U fantray

3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt 24VDC PSU and 8 slot backplane, 4U variant including 1U fantray

3U CompactPCI® Rack with RIO option, 84HP, M-style 180 Watt AC PSU and 8 slot backplane, 4U variant including 1U fantray

3U CompactPCI® Rack with RIO option, 84HP, M-style 100 Watt wide range PSU 16.8-137.5 VDC operating and 8 slot backplane, 4U variant including 1U fantray

4U CompactPCI® Rack with 1U fantray, for switched Multi-CPU assembly and M-style 100 Watt wide range PSU 16.8-137.5 VDC operating. Backplane: 3 CompactPCI® segments 6/2/2 slots with ETH connection from switch slot to system slots and space for HW RAID Kit with 4 SATA Disk slots. See also a separate datasheet.

3U CompactPCI® rack 42HP, 235mm depth wall-mount, with M-style 100W wide range PSU 16.8-137.5 VDC operating, 4 slot backplane,

4U variant including 1U fantray

4U CompactPCI® table top rack with RIO option and fans, 44HP, M-style 180 Watt AC PSU, 5 slot backplane

SATA HDD/SSD carrier, 1 slot backplane, SATA cable

2x SATA HDD/SSD carrier, 2 slot backplane, 2x SATA cable

CDROM Assembly Set, 5.25", 32HP Front

SATA re-writable CD/DVD ROM for CompactPCI®

*Drives and CompactPCI® boards can be integrated on request. Additional customized rack variants on request.

Moreover: dedicated system platforms

Ask for your entire platform solution for 3U CompactPCI®, based on a CP-ASM3 rack variant and the right selection out of Kontron's rich CPU blade portfolio, including periphery which fulfills your I/O, storage and networking requirements. Optionally, you may perform the hardware integration yourself. Or, in order to fully concentrate on your application, you may leave the integration to Kontron, and consequently address the platform responsibility to Kontron, which includes co-operability, obsolescence, environmental and EMC criteria of the system.

Dedicated project management

As a global company, Kontron has knowledgeable teams to support you in your region. Through your local project manager you have worldwide access to immense specialist know-how. Your project manager guides you securely through the entire design-in process to productionready product by means of a precise gate project plan. This allows you to concentrate on your core business and still retain an overview and full control of development, documentation, and production, including unique test processes, systems and procedures.

CORPORATE OFFICES

Europe, Middle East & Africa

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany

Tel.: +49 (0) 821 4086-0
Fax: +49 (0) 821 4086 111
sales@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA

Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China

Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn