

» KISS DA225 «



Ultra compact Disk Array

- » Space saving Disk Array
- » 2x 2.5" SAS/SATA HDDs
- » Passive cooled
- » Light weight durable aluminum

Daracheet - KISS DA202 SUNWHH All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is All data is for information purposes only and not guaranteed for legal purposes. Subject to change it is presented and is All brand or product names are trademarks or registered trademarks of their respective owners.

KISS DA225

KISS Disk Array

Designed to fit inside the space of a standard 5.25" drive bay, the new KISS DA 2.5" Disk Array is a unique drive cage solution that can accommodate up to 2x 2.5" SAS or SATA hard drives. Thus the 2.5" KISS DA can be easily deployed in many KISS Industrial Servers. Because of its compact form factor, it also fits nicely into our KISS 2U system. The KISS DA225 is constructed in light weight durable aluminum. The back plane connections include both SAS and SATA connectors and each drive drawer is equipped with power and drive access LEDs. The drive drawer is

designed to accommodate any standard 2.5" SATA devices including 2.5" SSD or regular CF media. The hard drives/ SSDs can be set up in various configurations: as RAID 0, RAID 1, RAID 5 or JBOD, as individual drive, or whatever the mix that best fits the application. The Disk Array can start with as little as one hard drive and can then expand as needed. Hard Drives can also be removed or added to the system without turning off your system power or restarting your computer.

-	•		
	hnica		

Interface

Construction Material

Hard Drive Type

Maximum Number of Drives

Maximum Drive Height

Maximum Data Transfer Rate

Power Connection

Connections

LEDs Lock

.....

Hard Drive Connection

Cooling System

Weight (with no hard drive)

Dimensions (L x W x H)

SAS, SATA

Heavy duty cold solled steel

SAS/SATA 3G/6G 2 in 1 Backplane

2x 2.5"

14 mm (supports 12.5mm hard drives)

6/3G

One 4-pin Molex power connector

Two 7-pin SATA connectors, two 7-pin SAS connectors

Power and Drive Activity LEDs for each drive drawer

Key lock for each drive drawer

Point to point, no cable required for installing hard drive into drive drawer

Passive cooled

1.54lb (0.7KG)

185 x146 x 42 mm

CORPORATE OFFICES

Europe, Middle East & Africa

Lise-Meitner-Str. 3-5 86156 Augsburg

Germany

Tel.: +49 (0) 821 4086-0 Fax: +49 (0) 821 4086 111

sales@kontron.com

North America

14118 Stowe Drive Poway, CA 92064-7147 USA

Tel.: +1 888 294 4558 Fax: +1 858 677 0898

info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP. 188 Southern West 4th Ring Road

Beijing 100070, P.R.China

Tel.: +86 10 63751188 Fax: +86 10 83682438 info@kontron.cn

2