

- ▶ **KB8HP**
- ▶ **NEMA 4 Small Footprint Keyboard with HulaPoint**



- ▶ **The First Plastic Enclosed NEMA 4/4x Industrial Keyboard**

The KB8HP is the first NEMA 4/4x industrial keyboard housed in a robust ABS-Polycarbonate plastic case and combines a comprehensive range of features and functions with the highest quality and exceptional reliability rolled into one unit.

The KB8HP's full-size QWERTY keypad provides true industrial grade performance with 116-key functionality. This powerful product design includes twenty-four function keys, Microsoft Windows keys

and an integrated 3-button HulaPoint™ pointing device. The zero footprint design allows for easy integration into rack drawers, shelves and other small locations to meet various application requirements. Easy to set up through Plug-n-Play, this unit requires no driver software or extra programming and provides compatibility with most operating systems. Engineered using the highest quality components, the KB8HP provides superior performance for data entry and system control in harsh, rugged environments.

- ▶ **116-key keypad and a 3-button pointing device**
- ▶ **Twenty-four function keys**
- ▶ **Microsoft® Windows® keys**
- ▶ **Industrial silicone rubber keypad and ABS-Polycarbonate plastic case**
- ▶ **Meets NEMA 4, 4x and 12 specifications**



► KB8HP - Technical Specifications

Industrial Ratings

- NEMA 4, 4x and 12
- UL-1950
- CE
- FCC Class 15, Part B

Key Switch

Material

- Industrial silicone rubber

Life

- >10 million cycles

Travel

- 0.06-inch (1.5mm)

Actuation Force

- 5oz (130g)

Feedback

- Tactile with mechanical snap

Physical Characteristics

Dimensions (W x H x D)

- 15 x 6.5 x 1.5-inches (381 x 165.1 x 38.1mm)

Weight

- 2.3lb (1.5kg)

Cable

- 9-feet (2.75-meter)
- "Y" cable (providing separate keyboard and mouse connections)

Power Requirements

Keyboard

- +5V @ 10ma (from CPU port)

HulaPoint

- +5V @ 10ma (from mouse connection port)

Environmental

Operating Temperature

- -40 ° to 90 °C (-40 ° to 194 °F)

Humidity

- 100%

Shock

- 3x 11ms pulses of 50g on each of three axis

Vibration

- Power Spectral Density: 0.04g/Hz
- Frequency Range: 20Hz to 2KHz
- Duration of Test Per Axis: 3hrs

Flammability

- Printed Circuit Board: 94VO
- Silicone Overlay: 94HB
- Interface Cable: 94VO

OS Support

Keyboard

- PS/2, AT, Windows®95/98/2000/NT/Me/XP

HulaPoint

- Microsoft®, PS/2, serial and Logitech®

Support

- Superior pre- and post sales technical support
- One year limited warranty

Ordering Guide

KB8HP

- NEMA sealed keyboard with HulaPoint™, small footprint, AT connector

KB8HP-PS2

- NEMA sealed keyboard with HulaPoint, small footprint, PS/2 connector



www.kontron.com



Corporate Offices

US / Canada
6260 Sequence Drive
San Diego, CA 92121-4371
Tel. (858) 677-0877
Fax (858) 677-0898
sales@us.kontron.com



Europe, Middle East and Africa

Oskar-von-Miller-Straße 1
D-85386 Eching/Munich Germany
Tel. +49 81-65 77 0
Fax +49 81-65 77 219
sales@de.kontron.com



Asia Pacific

6F No 9, Lane 235, Pao Chiao Road Hsin
Tien 231, Taipei, Taiwan
Tel. +886 2 2910 3532
Fax +886 2 2910 3482
sales@tw.kontron.com

