

» KISS Oil & Gas 2U «



2U Rugged Rackmount Solution

- » Designed for Oil & Gas Applications
- » Rugged chassis design for extreme environments
- » Based on KTQ77/FLEX
- » Supports Intel[®] 3rd Generation Core[™] i Series

Datasheet - KISS 08.6 2U #02252015WWH All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is believed to be accurate; however, no responsibilty is assumed for inaccurancies. All brand or product names are trademarks or registered trademarks of their respective owners.

KISS Oil & Gas 2U

The Kontron Oil & Gas Server is designed for the challenging environments of the Oil & Gas Industry. The rugged design includes front accessible dust filter, shock-mounted drive bays, cable tie-downs and hold-down

bracket for expansion card and memory. The 2U Rugged Rackmount also features long life, revision control and global technical support.

| Dimensions (H x W x D): | 88.9 mm x 483 mm x 483mm (3.5" x 19" x 19.06") | |
|-------------------------|--|--|
| | | |
| Weight: | 10kg (22lb) | |
| Front I/0: | 2x USB 2.0 Power Switch | |
| | Power LED, HDD activity LED | |
| Rear I/0: | 2x Display Port, 1x VGA, | |
| | 4x USB 3.0, 2x USB 2.0, | |
| | 3x Gigabit Ethernet, | |
| | 4x RS232 COM ports, | |
| | HD Audio | |
| Accessible drive bays: | 3x 2.5" or 3.5" Hard Disk Drives (HDD's) or Solid State Drives (SSD's) | |
| | 1 x Slim Optical Drive (DVD +/- RW) | |
| Power supply: | 500W high efficiency AC | |
| Expansion slots: | 1x PCI Express x16 Gen 3, | |
| | 1x 32-bit 5V PCI | |
| Motherboard: | KTQ77/FLEX | |
| Chipset: | Intel® Q77 | |
| Memory: | Up to 32 GB DDR3 RAM | |
| Processor: | Intel® 3rd Generation Core™ i Series | |
| Cooling: | 1x CPU Cooler Fan, 3x Chassis fans | |
| Temperature: | 0°C to 50°C (operating) -40°C to 70°C (non-operating) | |
| Humidity: | 10% to 90% relative humidity, non-condensing (operating), | |
| | 5% to 95% relative humidity, non-condensing (non-operating) | |
| Shock: | 15 G, 11ms | |
| Vibration: | 10-500 Hz, 5G | |
| Certifications: | FCC, CE, UL | |

CORPORATE OFFICES

| Europe, Middle East & Africa | North America | Asia Pacific |
|------------------------------|-----------------------------|--|
| Lise-Meitner-Str. 3-5 | 14118 Stowe Drive | 17 Building, Block #1, ABP. |
| 86156 Augsburg Germany | Poway, CA 92064-7147 USA | 188 Southern West 4th Ring Road Beijing 100070, P.R.China |
| Tel.: +49 (0) 821 4086-0 | Tel.: +1 888 294 4558 | Tel.: +86 10 63751188 |
| Fax: +49 (0) 821 4086 111 | Fax: +1 858 677 0898 | Fax: +86 10 83682438 |
| sales@kontron.com | info@us.kontron.com | info@kontron.cn |

2