KTQ87/Flex





EMBEDDED FLEX MOTHERBOARD WITH Intel® Q87 CHIPSET AND 4th GENERATION Intel® i7/i5/i3 Dual AND Quad Core™ CPUs

- ► 4th Generation Intel® 22 nm Dual and Quad Core™ i7, i5, i3, Pentium & Celeron® CPUs with Intel® Q87 Lynx Point PCH
- long term available Embedded Flex motherboard
- high performance CPU, graphics, and media performance supporting 3 independent displays pipes



Copyright © 2016 Kontron AG. All rights reserved All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Kontron and the Kontron logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. Specifications are subject to change without notice. KTQ87/Flex-20160517-WMH

- ► Gaming/POS/POI: High graphics and CPU performance, multi display support
- ▶ Medical: High Graphics performance & longevity
- ▶ Industrial Automation: Wide range of I/Os & longevity
- ► Future-oriented Devices Due to DisplayPort and LVDS



TECHNICAL INFORMATION

FORM FACTOR	Flex 229 x 191 mm (7.5" x 9.0")		
СРИ	Intel® Core i7/i5/i3 2C/4C CPU clock up to 3.1 GHz		
GRAPHICS	Integrated into CPU with GT1 or GT2 depending on CPU type		
GRAPHIC INTERFACE	3x DisplayPort revision 1.2 in Rear IO 1x 18/24Bit dual Link LVDS interface in internal header, Note: LVDS interface share one DisplayPort		
MEMORY	Up to 8 GByte DDR3L/DDR3, 4x DIMM (max. 32 GByte), PC3-10600/PC3-12800 support		
CHIPSET	Intel® Embedded Q87		
FRONT SIDE BUS	DMI 2.0 support, four lanes in each direction, up to 20 Gb/s each direction, full duplex, DMI interface to PCH is supported		
SATA	6x SATA interfaces SATA 1.5/3/6 Gbit/s w. RAID 0/1/5/10		
USB	4x USB 3.0 & 8 USB 2.0. (4x USB3.0/USB2.0 Rear IO, 8x USB2.0 Internal Header)		
AUDIO	HD Audio codec VT17085 supporting 7.1 channel surround sound		
ETHERNET	2x Intel Gigabit-LAN, one LAN controller supporting Intel® AMT 9.0		
AVAILABLE I/OS	PCle x16 socket with Gen3 and Gen2 support, 1x x4 PCle, 1x x1 PCle, 1x PCl rev 2.3, 2x COM (RS232)		
REAR I/O	Audio stacked 2x 3 mini Jack tower, 4x USB, 3x DisplayPort, 2x RJ45 LAN		
SPECIAL FEATURE	AMT 9.0, TPM 1.2, Intel® AES security, Kontron embedded feature connector with ADC, DAC up to 160 GPIOs		
OS SUPPORT	Win7, Win8 WES8, WES7, Linux, VxWorks		
TEMPERATURE	Operating 0 °C to 60 °C (32 °F to 140 °F)		
ADDITIONAL	Up to 7 years availability		

ORDERING INFORMATION

ARTICLE

KTH87/FLEX

			· · · · · · · · · · · · · · · · · · ·	
CPUS				
CPU, CORE I5	1054-9757		CPU, Core i5-4570S GT2 2.9G 4C 6M LGA1150	
CPU, CORE I7	1054-9752		CPU, Core i7-4770S GT2 3.1G 4C 8M LGA1150	
CPU, CORE i3	1055-5247		CPU, Core i3-4330 GT2 3.5G 2C 4M, LGA1150	
Further CPUs will be defined in near future.				
RECOMMENDED MEMORY MODULES	NEW SKU 04/16*	OLD SKU	SKU NAME**	
	1060-2492	1054-3702	DDR3-1333 DIMM 2 GByte	
	1060-2494	1054-3703	DDR3-1333 DIMM 4 GByte	
	1060-2496	1054-3704	DDR3-1333 DIMM 8 GByte	
	1060-2498	1054-3707	DDR3-1600 DIMM 2 GByte	
	1060-2500	1054-3708	DDR3-1600 DIMM 4 GByte	
	1060-2488	1052-5601	DDR3-1600 DIMM 8 GByte	

DESCRIPTION

Flex board based on Intel® Shark Bay platform

PART NO.

810581-4500

CORPORATE OFFICES	EUROPE, MIDDLE EAST & AFRICA	NORTH AMERICA	ASIA PACIFIC	
	Lise-Meitner-Str. 3-5	14118 Stowe Drive	1~2F, 10 Building, No. 8 Liangshuihe 2nd Street,	
	86156 Augsburg	Poway, CA 92064-7147	Economical & Technological Development Zone,	
	Germany	USA	Beijing, 100176, P.R.China	
	Tel.: + 49 821 4086 0	Tel.: + 1 888 294 4558	Tel.: +86 10 63751188	
	Fax: + 49 821 4086 111	Fax: + 1858 677 0898	Fax: +86 10 83682438	
	info@kontron.com	info@us.kontron.com	info@kontron.cn	

// 2

^{*}SKU changes were caused by administrative issues only, no hardware changes.

**Named are always the min. requirements, the shipped memory can fulfill a higher performance level.