


» User Guide «



CPS3003-SA

Doc. ID: 1054-3213, Rev. 2.0

Date: February 10, 2014

Revision History

Revision	Brief Description of Changes	Date of Issue
1.0	Initial issue	13-May-2014
2.0	Extensive changes	10-Feb-2014

Imprint

Kontron Europe GmbH may be contacted via the following:

MAILING ADDRESS

Kontron Europe GmbH
Sudetenstraße 7
D - 87600 Kaufbeuren Germany

TELEPHONE AND E-MAIL

+49 (0) 800-SALESKONTRON
sales@kontron.com

For further information concerning other Kontron products, please visit our Internet website:
www.kontron.com.

Disclaimer

Copyright © 2013-2014 Kontron AG. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Kontron and the Kontron logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. Specifications are subject to change without notice.

Contents

Revision History	2
Imprint	2
Disclaimer	2
Contents	3
Tables	7
Figures	8
Warranty	9
Proprietary Note	9
Trademarks	9
Environmental Protection Statement	9

1	Introduction	10
1.1	Board Overview	10
1.2	System Expansion Capabilities	11
1.2.1	CPS3003-EXTIO Extension Module (8 HP)	11
1.2.2	CPS3003-BRIDGE Extension Module (9 HP).....	11
1.2.3	CPS-RI03-01 Rear Transition Module	11
1.2.4	Smart Extension Module	11
1.2.5	SATA Flash Module	11
1.3	Board Diagrams.....	11
1.3.1	Functional Block Diagram	12
1.3.2	Front Panel	13
1.3.3	Board Layout	14
1.4	Technical Specification	15
1.5	Standards	18
1.6	Related Publications.....	19
2	Functional Description	20
2.1	Processor and Chipset	20
2.1.1	Integrated Processor Graphics Controller	20
2.2	Memory	20
2.3	Watchdog Timer.....	21
2.4	Battery.....	21
2.5	Flash Memory.....	21
2.5.1	SPI Boot Flash for uEFI BIOS	21
2.5.2	SATA Flash Module	21
2.6	Trusted Platform Module 1.2.....	22
2.7	Board Interfaces.....	22
2.7.1	Front Panel LEDs.....	22
2.7.1.1	System Status LEDs	22

2.7.1.2	General Purpose LEDs	22
2.7.2	USB Interfaces	24
2.7.3	DisplayPort Interfaces	24
2.7.4	Serial Ports	24
2.7.5	Gigabit Ethernet.....	24
2.7.6	SATA Interfaces	25
2.7.7	CompactPCI Serial Interface	25
2.7.7.1	CompactPCI Serial Connectors P1 to P5	26
2.7.7.2	CompactPCI Serial Connector P6	28
3	Configuration	31
3.1	DIP Switch Configuration	31
3.2	System Write Protection	31
3.3	CPS3003-SA-Specific Registers	32
3.3.1	Write Protection Register (WPROT)	32
3.3.2	Reset Status Register (RSTAT)	33
3.3.3	Watchdog Timer Control Register (WTIM)	34
3.3.4	LED Configuration Register (LCFG)	35
3.3.5	LED Control Register (LCTRL)	35
3.3.6	General Purpose Output Register (GPOUT).....	36
3.3.7	General Purpose Input Register (GPIN)	36
4	Power Considerations	37
4.1	CPS3003-SA Voltage Ranges	37
4.2	Power Consumption.....	37
5	Thermal Considerations	39
5.1	Operational Limits for the CPS3003-SA	40
5.2	Airflow Impedance	41
6	CPS3003-EXTIO Extension Module	42
6.1	Overview.....	42
6.2	Technical Specifications	42
6.3	CPS3003-EXTIO Module Functional Block Diagram.....	43
6.4	Front Panel of the CPS3003-SA with CPS3003-EXTIO Module	44
6.5	CPS3003-EXTIO Module Board Layout.....	44
6.6	Module Interfaces (Front Panel and Onboard).....	45
6.6.1	USB Interface	45
6.6.2	Serial Port.....	45
6.6.3	CFast Card Socket.....	45
7	CPS3003-BRIDGE Extension Module	46
7.1	Overview.....	46
7.2	Technical Specifications	46
7.3	CPS3003-BRIDGE Module Functional Block Diagram	47

7.4	Front Panel of the CPS3003-SA with CPS3003-BRIDGE Module	48
7.5	CPS3003-BRIDGE Module Board Layout	48
7.6	Module Interfaces (Front Panel and Onboard).....	49
7.6.1	USB Interface	49
7.6.2	Serial Port.....	49
7.6.3	CFast Card Socket.....	49
7.6.4	CompactPCI Interfaces	49
7.6.5	CompactPCI Connector Keying	49
8	CPS-RI03-01 Rear Transition Module	50
8.1	Overview.....	50
8.2	Technical Specifications	50
8.3	CPS-RI03-01 Module Functional Block Diagram	51
8.4	CPS-RI03-01 Rear Transition Module Layout.....	52
8.5	Module Interfaces	53
8.5.1	USB Interfaces	53
8.5.2	DisplayPort Interface	53
8.5.3	Gigabit Ethernet Interface	53
8.5.4	COM Interface	53
8.5.5	Rear I/O Interface on CompactPCI Serial Connector - rJ6	53
8.5.6	System Write Protection	53
8.5.7	Jumper J1	53
9	Smart Extension Module	54
9.1	Overview.....	54
9.2	Technical Specifications	54
9.3	Smart Extension Module Layout	54
9.4	Module Interfaces	54
9.4.1	USB Interface	54
9.4.2	SATA Interface	54
10	SATA Flash Module	55
10.1	Overview.....	55
10.2	Technical Specifications	55
10.3	SATA Flash Module Layout.....	56
11	Installation	57
11.1	Safety	57
11.2	General Instructions on Usage	57
11.3	Board Installation	57
11.3.1	Hot Swap Insertion	58
11.3.2	Hot Swap Removal	58
11.4	CFast Card Installation	59
11.5	Rear Transition Module Installation	59
11.6	Battery Replacement	59

12	uEFI BIOS	60
12.1	Starting the uEFI BIOS	60
12.2	Setup Menus	61
12.2.1	Main Menu	61
12.2.2	Boot Menu	63
12.2.3	Security Menu	64
12.2.3.1	Modes of Security	65
12.2.3.2	Remember the Password	65
12.2.4	Save and Exit Menu	65
12.3	The uEFI Shell	67
12.3.1	Introduction, Basic Operation	67
12.3.1.1	Entering the uEFI Shell	67
12.3.1.2	Exiting the uEFI Shell	67
12.3.2	Kontron-Specific uEFI Shell Commands	68
12.4	uEFI Shell Scripting	69
12.4.1	Startup Scripting	69
12.4.2	Create a Startup Script	69
12.4.3	Examples of Startup Scripts	70
12.4.3.1	Automatic Booting from USB Flash Drive	70
12.4.3.2	Execute Shell Script on Other Harddrive	70
12.4.3.3	Enable Watchdog and Control PXE Boot	70
12.4.3.4	Handling the Startup Script in the SPI Boot Flash	71
12.5	Updating the uEFI BIOS	72
12.5.1	Updating Procedure	72
12.5.2	UEFI BIOS Recovery	72
12.5.3	Determining the Active Flash	72

Tables

1	CPS3003-SA Main Specifications	15
2	Standards	18
3	Additional Standards for Boards Ordered with Ruggedized Service	19
4	Related Publications	19
5	Features of the Processors Supported on the CPS3003-SA	20
6	System Status LEDs Function	22
7	General Purpose LEDs Function	23
8	POST Code Sequence	23
9	POST Code Example	23
10	Legend for CompactPCI Serial Connectors P1 to P5	26
11	Pinout for CompactPCI Serial Connector P1	27
12	Pinout for CompactPCI Serial Connector P2	27
13	Pinout for CompactPCI Serial Connector P3	27
14	Pinout for CompactPCI Serial Connector P4	28
15	Pinout for CompactPCI Serial Connector P5	28
16	Legend for CompactPCI Serial Connector P6	28
17	Pinout for CompactPCI Serial Connector P6	29
18	GPIO_CFG# Signal Description	30
19	SYS_WP# Signal Description	30
20	DIP Switch SW1 Functionality	31
21	CPS3003-SA-Specific Registers	32
22	Write Protection Register (WPROT)	32
23	Reset Status Register (RSTAT)	33
24	Watchdog Timer Control Register (WTIM)	34
25	LED Configuration Register (LCFG)	35
26	LED Control Register (LCTRL)	35
27	General Purpose Output Register (GPOUT)	36
28	General Purpose Input Register (GPIN)	36
29	DC Operational Input Voltage Range	37
30	CPS3003-SA Power Consumption	38
31	Power Consumption of CPS3003-SA Accessories	38
32	CPS3003-EXTIO Module Specifications	42
33	Serial Port Connector J3 Pinout	45
34	CPS3003-BRIDGE Module Specifications	46
35	Serial Port Connector J3 Pinout	49
36	CPS-RIO3-01 Rear Transition Module Specifications	50
37	Serial Port Connectors J7 (COMB) and J8 (COMA) Pinout	53
38	Smart Extension Module Specifications	54
39	SATA Flash Module Specifications	55
40	Navigation	60
41	Main Menu Sub-Screens and Functions	61
42	Boot Menu Functions	63
43	Security Menu Functions	64
44	Modes of Security	65
45	Save and Exit Menu Functions	65
46	Kontron-Specific uEFI Shell Commands	68

Figures

1	CPS3003-SA Functional Block Diagram	12
2	4 HP CPS3003-SA Front Panel	13
3	4 HP CPS3003-SA Board Layout (Top View)	14
4	4 HP CPS3003-SA Board Layout (Bottom View)	14
5	CompactPCI Serial Connectors P1 to P6	25
6	DIP Switch SW1	31
7	CPS3003-SA with i7-3612QE (SV), 2.1 GHz	40
8	CPS3003-SA with i7-3555LE (LV), 2.5 GHz	40
9	CPS3003-SA with i7-3517UE (ULV), 1.7 GHz	41
10	CPS3003-SA Airflow Impedance	41
11	CPS3003-EXTIO Module Functional Block Diagram	43
12	Front Panel of the 8 HP CPS3003-SA with CPS3003-EXTIO Module	44
13	CPS3003-EXTIO Module Board Layout (Top View)	44
14	Serial Port Connector J3	45
15	CPS3003-BRIDGE Module Functional Block Diagram	47
16	Front Panel of the 9 HP CPS3003-SA with CPS3003-BRIDGE Module	48
17	CPS3003-EXTIO Module Board Layout (Top View)	48
18	Serial Port Connector J3	49
19	CPS-RIO3-01 Module Functional Block Diagram	51
20	CPS-RIO3-01 Rear Transition Module Layout	52
21	Smart Extension Module Layout (Top View)	54
22	SATA Flash Module Layout (Top and Bottom Views)	56

Warranty

This Kontron product is warranted against defects in material and workmanship for the warranty period from the date of shipment. During the warranty period, Kontron will at its discretion decide to repair or replace defective products.

Within the warranty period, the repair of products is free of charge as long as warranty conditions are observed.

The warranty does not apply to defects resulting from improper or inadequate maintenance or handling by the buyer, unauthorized modification or misuse, operation outside of the product's environmental specifications or improper installation or maintenance.

Kontron will not be responsible for any defects or damages to other products not supplied by Kontron that are caused by a faulty Kontron product.

Proprietary Note

This document contains information proprietary to Kontron. It may not be copied or transmitted by any means, disclosed to others, or stored in any retrieval system or media without the prior written consent of Kontron or one of its authorized agents.

The information contained in this document is, to the best of our knowledge, entirely correct. However, Kontron cannot accept liability for any inaccuracies or the consequences thereof, or for any liability arising from the use or application of any circuit, product, or example shown in this document.

Kontron reserves the right to change, modify, or improve this document or the product described herein, as seen fit by Kontron without further notice.

Trademarks

This document may include names, company logos and trademarks, which are registered trademarks and, therefore, proprietary to their respective owners.

Environmental Protection Statement

This product has been manufactured to satisfy environmental protection requirements where possible. Many of the components used (structural parts, printed circuit boards, connectors, batteries, etc.) are capable of being recycled.

Final disposition of this product after its service life must be accomplished in accordance with applicable country, state, or local laws or regulations.

1 Introduction

1.1 Board Overview

CompactPCI® Serial, adopted by the PICMG® consortium in 2011, describes a new base standard. The CompactPCI Serial standard introduces a completely new connector that enables a higher signal density and supports even higher transmission frequencies of up to 12 Gb/s as well as modern point-to-point connections such as PCI Express®, SATA, Ethernet and USB on the backplane.

The CPS3003-SA is a highly integrated 3U CompactPCI Serial CPU board based on Intel®'s 3rd Generation Core™ i7 technology in combination with the mobile Intel® QM77 Express Chipset. The CPU board comes with a multi-core CPU package scalable from the dual-core ULV 1.7 GHz Intel® Core™ i7-3517UE up to the quad-core 2.1 GHz i7-3612QE processor. The powerful PCH Intel® QM77 provides a variety of interfaces either routed to front, onboard or the CompactPCI Serial connectors. Memory-demanding applications can make use of up to 16 GB, 1600 MHz DDR3 SDRAM with Error Checking and Correction (ECC). As another security feature, the CPS3003-SA provides a Trusted Platform Module (TPM) which offers hardware-based encryption mechanisms to create, seal or store keys and other important system data.

For graphics intensive applications, the CPS3003-SA offers an excellent graphics performance with integrated DirectX®11, OpenGL 3.1 and OpenCL 1.1 support as well as three independent graphics outputs.

The CPS3003-SA comes with a comprehensive I/O feature set supporting the latest high-speed interfaces such as USB 3.0, SATA 6Gb/s or PCI Express® 3.0. Communication interfaces available on the front panel are two DisplayPort, two USB 2.0 and two Gigabit Ethernet ports. Serial interfaces available on the CompactPCI Serial connectors P1 to P5 are eight USB ports, four SATA interfaces and 17x PCI Express® links. Additional interfaces available on the P6 CompactPCI Serial rear I/O connector are two Gigabit Ethernet interfaces, two USB ports, one DisplayPort and two serial ports.

By adding one of the four extension modules – Smart Extension Module, SATA Flash Module, CPS3003-EXTIO or CPS3003-BRIDGE - the CPS3003-SA's I/O and storage capabilities will be further extended.

The board is offered with various Board Support Packages including Windows, VxWorks and Linux operating systems. For further information concerning the operating systems available for the CP3003-SA, please contact Kontron.

1.2 System Expansion Capabilities

1.2.1 CPS3003-EXTIO Extension Module (8 HP)

The CPS3003-EXTIO module for the 8 HP CPS3003-SA version provides one USB 3.0 port, one COM port, and one CFast socket on the front panel. For further information on the CPS3003-EXTIO extension module, refer to Chapter 6.

1.2.2 CPS3003-BRIDGE Extension Module (9 HP)

The CPS3003-BRIDGE module for the 9 HP CPS3003-SA version provides one USB 3.0 port, one COM port, and one CFast socket on the front panel. In addition, the CPS3003-BRIDGE module is equipped with a PCI Express-to-PCI bridge which converts PCI Express signals into PCI signals and makes them available on the CompactPCI interface. For further information on the CPS3003-BRIDGE extension module, refer to Chapter 7.

1.2.3 CPS-RIO3-01 Rear Transition Module

The CPS-RIO3-01 rear transition module provides comprehensive rear I/O functionality, such as one DisplayPort, two COM ports, two Gigabit Ethernet ports, one USB 3.0 port, and one USB 2.0 port. For further information on the CPS-RIO3-01 rear transition module, refer to Chapter 8.

1.2.4 Smart Extension Module

The Smart Extension Module can be used with the 4 HP CPS3003-SA and expands the onboard I/O capability providing one additional SATA cable connector as well as one USB 2.0 connector thereby facilitating the connection to system-internal USB and SATA devices. For further information on the Smart Extension Module, refer to Chapter 9.

Note: If a Smart Extension Module is installed on the CPS3003-SA, the board width exceeds 4 HP.

1.2.5 SATA Flash Module


The SATA Flash module can be used with the 4 HP CPS3003-SA and provides up to 32 GB of SLC NAND flash memory. For further information on the SATA Flash module, refer to Chapter 10.

1.3 Board Diagrams

The following diagrams provide additional information concerning board functionality and component layout.


1.3.1 Functional Block Diagram

Figure 1: CPS3003-SA Functional Block Diagram



1.3.2 Front Panel

Figure 2: 4 HP CPS3003-SA Front Panel



System Status LEDs

HS (blue):	Hot Swap Status
TH (red/green):	Temperature Status
WD (green):	Watchdog Status

General Purpose LEDs

LED3..0 (red/green/red+green): General Purpose/ POST Code

Note: If the General Purpose LEDs 3..0 are lit red during boot-up, a failure is indicated before the uEFI BIOS has started.

Integral Ethernet LEDs

ACT (green):	Ethernet Link/Activity
SPEED (orange):	1000BASE-T Ethernet Speed
SPEED (green):	100BASE-TX Ethernet Speed
SPEED (off) + ACT on:	10BASE-T Ethernet Speed

Note: For information regarding the front panel of the 8 HP CPS3003-SA with a CPS3003-EXTIO extension module, refer to Chapter 6.

For information regarding the front panel of the 9 HP CPS3003-SA with a CPS3003-BRIDGE extension module, refer to Chapter 7.

1.3.3 Board Layout

Figure 3: 4 HP CPS3003-SA Board Layout (Top View)





Figure 4: 4 HP CPS3003-SA Board Layout (Bottom View)



1.4 Technical Specification

Table 1: CPS3003-SA Main Specifications

FEATURES		SPECIFICATIONS
Processor & Chipset	CPU	<p>The CPS3003-SA supports the following 3rd generation processors:</p> <ul style="list-style-type: none"> » Quad-core Intel® Core™ i7-3612QE (SV), 2.1 GHz, 6 MB L3 cache » Dual-core Intel® Core™ i7-3555LE (LV), 2.5 GHz, 4 MB L3 cache » Dual-core Intel® Core™ i7-3517UE (ULV), 1.7 GHz, 4 MB L3 cache
	Graphics Controller	High-performance 3D graphics controller integrated in the processor
	PCH	Mobile Intel® QM77 Express Chipset
Memory	Main Memory	Up to 16 GB, dual-channel DDR3 SDRAM memory with ECC running at 1600 MHz on two SODIMM sockets
	Flash Memory	Two 8 MB SPI boot flash chips for two separate uEFI BIOS images Up to 32 GB SLC NAND flash via an onboard SATA Flash module (SSD)
	EEPROM	EEPROM with 64 kbit
Interfaces	CompactPCI Serial	<p>CompactPCI Serial interface:</p> <ul style="list-style-type: none"> » Compliant with PICMG® CPCI-S.0 R 1.0 CompactPCI® Serial Specification » Support for the following interfaces: <ul style="list-style-type: none"> » 7x PCI Express® (1 x8 PCI Express 3.0 on fat pipe, 1 x4 PCI Express 3.0 on fat pipe and 5 x1 PCI Express 2.0) » 4 x SATA (2 x SATA 6 Gb/s, 2 x SATA 3 Gb/s) » 2 x USB 3.0 / 2.0 » 6 x USB 2.0 » 2 x Gigabit Ethernet » 12 V power supply » Hot swap capability » Capability of operation both in system slot and in peripheral slot When installed in a peripheral slot, all interfaces except for the Ethernet interfaces and rear I/O interfaces are isolated from the CompactPCI Serial interface.
	CompactPCI Serial Rear I/O	<p>The following interfaces are routed to the CompactPCI Serial rear I/O connector P6:</p> <ul style="list-style-type: none"> » COMA and COMB, or COMA and GPIO (all ports have 3.3V LVTTL signaling) » 1 x USB 2.0 » 1 x USB 3.0 / 2.0 » DisplayPort » 2x Gigabit Ethernet » System control signals » Input for RTC backup
	Gigabit Ethernet	Two 10 Base-T/100 Base-TX/1000 Base-T Gigabit Ethernet interfaces based on two Intel® I210-IT Ethernet controllers. Both interfaces are individually switchable to front I/O or rear I/O and provide Wake-on-LAN support.

Table 1: CPS3003-SA Main Specifications (Continued)

FEATURES		SPECIFICATIONS
Interfaces	USB	<p>Up to 13 USB ports:</p> <ul style="list-style-type: none"> » 6 x USB 2.0 on the CompactPCI Serial interface » 2 x USB 3.0 / 2.0 on the CompactPCI Serial interface » 2 x USB 2.0 ports on the front I/O » 1 x USB 2.0 port on the rear I/O interface » 1 x USB 3.0 / 2.0 port on the rear I/O interface » 1 x USB 3.0 / 2.0 port on the CPS3003-EXTIO/CPS3003-BRIDGE extension module
	Serial	<p>Two 16C550-compatible UARTs:</p> <ul style="list-style-type: none"> » COMA available on the CPS3003-EXTIO/CPS3003-BRIDGE extension module or on rear I/O » COMB or GPIO available on the rear I/O only
	SATA	<p>Six SATA ports:</p> <ul style="list-style-type: none"> » 2 x SATA 3 Gb/s onboard » 2 x SATA 6 Gb/s on the CompactPCI Serial interface » 2 x SATA 3 Gb/s on the CompactPCI Serial interface <p>High-performance RAID 0/1/5/10 functionality on all SATA ports</p>
	I/O Extension Interfaces	<p>I/O extension to 8 HP board version via the CPS3003-EXTIO module:</p> <ul style="list-style-type: none"> » CFast (SATA 3 Gb/s) » USB 3.0 » COMA (RS-232) » Reset button » SATA activity LED <p>I/O extension to 9 HP board version via the CPS3003-BRIDGE module:</p> <ul style="list-style-type: none"> » CFast (SATA 3 Gb/s) » USB 3.0 » COMA (RS-232) » Reset button » SATA activity LED » CompactPCI interface <p>I/O extension of CPS3003-SA via the Smart Extension Module:</p> <ul style="list-style-type: none"> » SATA 3 Gb/s » USB 2.0 » When installed 4HP width is exceeded
Sockets	Front Panel Connectors	<p>DP: two DisplayPort connectors, J7 and J8</p> <p>USB: two 4-pin, type A connectors, J9 and J10</p> <p>Ethernet: dual RJ-45 connector, J11A/B</p>
	Onboard Connectors	<ul style="list-style-type: none"> » CompactPCI Serial connectors P1 to P6 » 18-pin extension connector for the SATA flash module (SSD), J16 » Two 204-pin DDR3 SODIMM sockets » 60-pin, high-speed I/O extension connector

Table 1: CPS3003-SA Main Specifications (Continued)

FEATURES		SPECIFICATIONS
LEDs/ Switches	Front Panel LEDs	<p>System Status LEDs:</p> <ul style="list-style-type: none"> » HS (blue): Hot Swap Status » TH (red/green): Temperature Status » WD (green): Watchdog Status <p>General Purpose LEDs:</p> <ul style="list-style-type: none"> » LED3..0 (red/green/red+green): General Purpose / POST Code <p>Ethernet LEDs:</p> <ul style="list-style-type: none"> » ACT (green): Network / Link Activity » SPEED (green/orange): Network Speed
	DIP Switch	One DIP switch, SW1, for board configuration
Timer	Real Time Clock	Real-time clock with 256 Byte CMOS RAM; battery-backup available
	Watchdog Timer	Software-configurable, two-stage Watchdog with programmable timeout ranging from 125 ms to 4096 s in 16 steps Serves for generating IRQ or hardware reset
Sys. Management	Thermal Management	CPU and board overtemperature protection is provided by: <ul style="list-style-type: none"> » Up to four Digital Thermal Sensors (DTS), one for each core » One Digital Thermal Sensor (DTS) for the processor graphics controller » One temperature sensor integrated in the Intel® QM77 Chipset for monitoring the chipset » Specially designed heat sinks
Security	TPM	Trusted Platform Module (TPM) 1.2 for enhanced hardware- and software-based data and system security
Software	uEFI BIOS	AMI Aptio® BIOS firmware based on the uEFI Specification and the Intel Platform Innovation Framework for EFI: <ul style="list-style-type: none"> » LAN boot capability for diskless systems (standard PXE) » Redundant image; recovery possible in case of a damaged image » Non-volatile storage of setting in the SPI boot flash (battery only required for the RTC) » Compatibility Support Module (CSM) providing legacy BIOS compatibility based on AMIBIOS8 » Command shell for diagnostics and configuration » uEFI Shell commands executable from mass storage device in a Pre-OS environment (open interface)
	Operating Systems	There are various operating systems available for the CPS3003-SA. For further information, please contact Kontron.

Table 1: CPS3003-SA Main Specifications (Continued)

FEATURES		SPECIFICATIONS	
General	Power Consumption	See Chapter 4 for details.	
	Temperature Range	Operational: 0°C to +60°C -40°C to +85°C	Standard (depending on processor version and air-flow in the system) Extended (with Intel® Core™ i7-3517UE, 1.7 GHz ULV processor only)
		Storage: -40°C to +85°C	Without hard disk and without battery
	Battery	3.0V lithium battery for RTC; Battery type: UL-approved CR1632 Temperature ranges: Operational (load): -20°C to +70°C typical (refer to the battery manufacturer's specifications for exact range) Storage (no load): -40°C to +70°C typical	
	Climatic Humidity	93% RH at 40 °C, non-condensing (acc. to IEC 60068-2-78)	
	Dimensions	100 mm x 160 mm 3U, 4 HP, CompactPCI Serial-compliant form factor	
Board Weight		4 HP CPS3003-SA with: » Intel® Core™ i7-3612QE (SV), 2.1 GHz, copper heat sink: 530 grams » Intel® Core™ i7-3555LE (LV), 2.5 GHz, aluminum heat sink: 330 grams » Intel® Core™ i7-3517UE (ULV), 1.7 GHz, aluminum heat sink: 330 grams The above-mentioned board weight refers to the 4 HP CPS3003-SA without extension modules such as SATA Flash module or Smart Extension Module.	

Note: For a description of the additional interfaces available on the 8 HP and 9 HP board versions, refer to Chapter 6, CPS3003-EXTIO Extension Module, and Chapter 7, CPS3003-BRIDGE Extension Module, respectively.

1.5 Standards

This product complies with the requirements of the following standards.

Table 2: Standards

TYPE	ASPECT	STANDARD
CE	Emission	EN55022, EN50121-3-2, EN61000-6-3
	Immission	EN55024, EN50121-3-2, EN61000-6-2
	Electrical Safety	EN60950-1
Mechanical	Mechanical Dimensions	IEEE 1101.10
Environmental	Climatic Humidity	IEC60068-2-78
	WEEE	Directive 2002/96/EC Waste electrical and electronic equipment
	RoHS 2	Directive 2011/65/EU Restriction of the use of certain hazardous substances in electrical and electronic equipment

In addition, boards ordered with the ruggedized service comply with the following standards as well.

Table 3: Additional Standards for Boards Ordered with Ruggedized Service

TYPE	ASPECT	STANDARD	REMARKS
Environmental	Vibration (Sinusoidal)	IEC60068-2-6 IEC61131-2	Ruggedized version test parameters: 9-150 (Hz) frequency range 1 (g) acceleration 1 (oct/min) sweep rate 10 cycles/axis 3 axis
	Single Shock	IEC60068-2-27 IEC61131-2	Ruggedized version test parameters: 15 (g) acceleration 11 (ms) shock duration half sine 3 number of shocks per direction (total: 18) 6 directions 5 (s) recovery time

Note: Customers desiring to perform further environmental testing of the CPS3003-SA must contact Kontron for assistance prior to performing any such testing.

Boards **without conformal coating** must not be exposed to a change of temperature which can lead to condensation. Condensation may cause irreversible damage, especially when the board is powered up again.

Kontron does not accept any responsibility for damage to products resulting from destructive environmental testing.

1.6 Related Publications

The following publications contain information relating to this product.

Table 4: Related Publications

PRODUCT	PUBLICATION
CompactPCI Serial Systems	PICMG® CPCI-S.0 R 1.0 CompactPCI® Serial Specification
CompactPCI Systems	PICMG® 2.0, Rev. 3.0 CompactPCI® Specification
CFast	CFast Specification Revision 1.1
Platform Firmware	Unified Extensible Firmware Interface (uEFI) specification, version 2.3.1
All Kontron products	Product Safety and Implementation Guide, ID 1021-9142